



CUTTING

# CNT



**Power supply unit for multifunctional hydraulic shears**



**Double pump**  
LOW CONSUMPTION, HIGH PERFORMANCE



**High productivity**  
LARGE OIL TANK



**Max safety**  
AUTOMATIC ON/OFF

- Efficient
- High safety standards
- Easy to use
- Easy maintenance
- Low consumption

**A Cutting catalytic converter, exhaust pipes and lightweight body parts**



ICU05A30 CAT



ICU10A30 CAT



RSX 130

**B Cutting and removal of cables and wiring harnesses**



ICU05A10 CABLE



ICU10A10 CABLE

**C Removal, bumpers, dashboards doors and tailgates**



ICU05A60 DIV



Automatic ON/OFF



6 meter pipes



 VIDEO



Automatic ON/OFF

Double pump



6 meter pipes

**OPTIONAL**

- BM1015 - Balancer with spring 22 Lbs-33 Lbs
- BM1418 - Balancer with spring 30.8 Lbs-39.7 Lbs
- KSC - Shear support



ICU05A30 CAT


ICU10A30 CAT



RSX 130



ICU05A10 CABLE



ICU10A10 CABLE



ICU05A60 DIV



		CNT 318006	
	Power supply	max	0,95 kW
	Voltage	max	Trifase - 400 V - 50 Hz
	Rated current		2,2 A
<b>Circuito idraulico 1° stadio</b>			
	Max flow		3,25 l / min
	Max working pressure		160 bar
<b>Circuito idraulico 2° stadio</b>			
	Max flow		0,67 l / min
	Max working pressure	Adjustable by the manufacturer	500 ÷ 700 bar
	Oil tank capacity		15 L
	Tubes length (cutter connection)		6 m
	'A' Weighted sound pressure level (LPA)		68 dB

**A** Catalytic converter, exhaust pipes and lightweight body parts

**B** Cables and wiring harnesses

**C** Bumpers, dashboards doors and tailgates



		ICU05A30 CAT 325006	ICU10A30 CAT 325007	RSX 130 325002	ICU05A10 CAB 325008	ICU10A10 CAB 325011	ICU05A60 DIV 325013	
		A			B		C	
	Blade opening	max	98	158	127	95	115	296 mm
	Cutting force	max	124	246	483	104	242	264 kN
	Weight		9,4	15,3	14,1	10,3	17,3	15,4 Kg