

CUTTING

CNT

Power supply unit for multifunctional hydraulic shears

Double pump
LOW CONSUMPTION, HIGH PERFORMANCE

High productivity
LARGE OIL TANK

Max safety
AUTOMATIC ON/OFF

Efficient | High safety standards | Easy to use | Easy maintenance | Low consumption

VIDEO

A Cutting catalytic converter, exhaust pipes and lightweight body parts


ICU05A30 CAT


ICU10A30 CAT


RSX 130

B Cutting and removal of cables and wiring harnesses


ICU05A10 CABLE


ICU10A10 CABLE

C Removal, bumpers, dashboards doors and tailgates



ICU05A60 DIV



Automatic ON/OFF


6 meter pipes

Iris-Mec srl - Via Grande 25, 42028 Poviglio (RE) - Italy
+39 0522 48.10.47
commerciale@iris-mec.it
www.iris-mec.com





Automatic ON/OFF



Double pump



6 meter pipes



OPTIONAL

- BM1015 - Balancer with spring 22 Lbs-33 Lbs
- BM1418 - Balancer with spring 30.8 Lbs-39.7 Lbs
- KSC - Shear support



A



ICU05A30 CAT



ICU10A30 CAT

A



RSX 130

B



ICU05A10 CABLE



ICU10A10 CABLE

C



ICU05A60 DIV

			CNT 318006	
	Power supply	max	0,95	kW
	Voltage	max	Trifase - 400 V - 50 Hz	
	Rated current		2,2	A
Circuito idraulico 1° stadio				
	Max flow		3,25	l / min
	Max working pressure		160	bar
Circuito idraulico 2° stadio				
	Max flow		0,67	l / min
	Max working pressure	Adjustable by the manufacturer	500 ÷ 700	bar
	Oil tank capacity		15	L
	Tubes length (cutter connection)		6	m
	'A' Weighted sound pressure level (LPA)		68	dB

A Catalytic converter, exhaust pipes and lightweight body parts

B Cables and wiring harnesses

C Bumpers, dashboards doors and tailgates













			ICU05A30 CAT 325006	ICU10A30 CAT 325007	RSX 130 325002	ICU05A10 CAB 325008	ICU10A10 CAB 325011	ICU05A60 DIV 325013	
			A			B		C	
	Blade opening	max	98	158	127	95	115	296	mm
	Cutting force	max	124	246	483	104	242	264	kN
	Weight		9,4	15,3	14,1	10,3	17,3	15,4	Kg

Iris-Mec srl - Via Grande 25, 42028 Poviglio (RE) - Italy +39 0522 48.10.47 commerciale@iris-mec.it www.iris-mec.com

03/2024